

polytouch[®] 24 rock

PRELIMINARY



HIGHLIGHTS

- Indoor/outdoor usage
- From -30° to +50° C
- Up to 7 mm laminated safety glass
- Self-sufficient control system



Figure shows configuration variant

polytouch[®] 24 rock

CHASSIS	Material	Stainless steel
	Dimensions (WxDxH)*	470 x 450 x 1930 mm (including illuminated sign on top)
	Temperature range	-30° ~ +50° C
	Mounting	Floor Installation
	Weight	TBD
DISPLAY	Size	609.7 mm (24")
	Resolution	1920 x 1080
	Brightness**	300 ~ 1300 cd/m ²
	Contrast	3000: 1
	View angle	178° h/v
TOUCHSCREEN	Technology	Projected Capacitive Touch
	Coating	Anti-Glare
	Glass***	6 mm single-pane or 7 mm laminated safety glass with UV/IR Filter
PC-BOX	Processor	Intel® Core™ i5-6500TE Skylake 4C/4T 2,3Ghz 6MB
	Chipset	Q170
	Memory	8 GB RAM
	Mass storage	256 GB mSATA SSD
	Network	2x 1GbE LAN
	LTA	Mainboard available until 2022
SELF-SUFFICIENT CONTROL SYSTEM	Up to 3 humidity sensors	
	Up to 3 temperature sensors	
	Dehumidification system	
	Heating module	
	Cooling module	
	LED Control	
OPT. COMPONENTS	Printer with 180 mm OD Paper Roll	
	Scanner/Imager	
	Cash-/Coins-System	
COLOURING	Powder-coated (customer specific)	

*optionally glass roof

**up on request

***other options available

ds_pt24_rock_en_rel_1.0 · specifications are subject to change